

Technical drawing of a vertical structure, likely a chimney or tower, showing dimensions and labels. The structure is divided into sections with heights of 4500, 4500, 3000, 4500, 4500, and 3000. Labels G1, G2, and G3 are placed along the structure. A scale bar indicates 1:10,000.

构件号	图 号	名 称	数量	重	量(公斤)	工地连接法
				单	总	
G1	D3320-70-00-63-T-101/16-1	放散管平台	1	407	407	焊接、螺栓
G2	D3320-70-00-63-T-101/16-1	放散管连接件	4	10.6	42.4	焊接
G3	D3320-70-00-63-T-101/16-1	放散管连接件	3	4.9	14.7	焊接、螺栓

- 1、本图所有构件均冠以字首“G”。
- 2、未注明焊缝均为满焊，除注明号外焊缝最小高度 $h_f=6$ 。
- 3、未注明安装螺栓为M16, 孔 $\phi 17.5$ 。
- 4、本图明细表仅统计一组放散装置放散管平台和管卡
其余三组与此相同

Figure 1 shows a technical drawing of a mechanical part. The part is a rectangular block with a slanted cut on the top surface. The dimensions are: top width 110, top depth 60, bottom width 122, bottom depth 70, and a slanted cut on the top surface with a horizontal projection of 58 and a vertical projection of 120.

G2 (共4个)	23	L50×6	510	6	2.3	14.7	14.7	42.4
	22	Φ20	440(25-60)	4	1	4		
	21	L75×6	1392	4	9.6	38.4		
	20	Φ20	580	11	1.4	15.4		
G1 (共16个)	19	-50×6	100	2	0.2	0.4	407	
	18	-30×4	1500	3	1.4	4.2		
	17	-50×4	1543	4	2.42	9.68		
	16	L50×6	4324	2	19.3	38.6		
	15	L50×6	350	2	1.6	3.2		
	14	Φ1920×5	开孔Φ880	1	96.7	96.7		花纹钢板
	13	-30×4	5760	2	5.4	10.8		
	12	-75×6	150	6	0.5	3		
	11	-180×6	190	6	1.6	9.6		
	10	-148×6	210	6	1.5	9		
	9	-160×6	158	6	1.2	7.2		
	8	-100×6	200	6	0.9	5.4		
	7	-100×6	250	6	1.2	7.2		
	6	L50×6	5760	1	25.7	25.7		
	5	L50×6	1100	7	4.9	34.3		
	4	L63×6	970	6	5.55	33.3		
3	L75×6	785	6	5.42	32.5			
2	L75×6	2513	1	17.4	17.4			
1	L75×6	6283	1	43.4	43.4			

构件号	件号	断面尺寸 (mm)	长度 (mm)	数量	单重	总重	共重	备注
					重	量	(kg)	
明 细 表								
 九江石化设计工程有限公司				建设单位	腾龙芳烃(漳州)有限公司			
				项目名称	腾龙芳烃(漳州)80万吨/年对二甲苯工程			
设计			20000m³ 卷帘型干式 气柜放散装置 放散管平台及管卡详图	设计阶段	详细设计			
校核				专 业	设备			
审核				单 元 号				
审 定				比例				
				D3320-70-00-63-T-101/16-				