


W5 (W50)

[illegible]

比例 1:1



会签专业	签署人	日期

4.除注明者外,其它所有焊缝腰高均等于相焊件中较薄者厚度,并是连续焊。

W6a (2个)						493	986	
	31	弹簧垫圈 16	/	16	0.0074	0.2		GB/T859-1987
	30	螺母M16	/	8	0.029	0.3		GB/T6170-2000
	29	螺栓 M16x60	/	8	0.117	1		GB/T5782-2000
	14	-280x5	1860	1	22	22		花纹钢板
	13	-270x6	2500	1	26.5	27		花纹钢板冷弯成型
	12	-1659.1x5	5858.7	1	411.6	412		花纹钢板冷弯成型
	6	-120x6	295	1	1.7	2		
	5	-90x6	1000	1	4.2	4		
	4	-90x6	1050	2	4.5	9		
	3	-90x6	1100	1	4.7	5		
	2	-90x6	1200	2	5.1	10		
W6 (2个)						498	996	
	31	弹簧垫圈 16	/	16	0.0074	0.2		GB/T859-1987
	30	螺母M16	/	8	0.029	0.3		GB/T6170-2000
	29	螺栓 M16x60	/	8	0.117	1		GB/T5782-2000
	14	-280x5	1860	1	22	22		花纹钢板
	13	-270x6	2500	1	26.5	27		花纹钢板冷弯成型
	11	-1659.1x5	5858.7	1	411.6	412		花纹钢板冷弯成型
	6	-120x6	295	1	1.7	2		
	5	-90x6	1000	1	4.2	4		
	4	-90x6	1050	3	4.5	14		
	3	-90x6	1100	1	4.7	5		
	2	-90x6	1200	2	5.1	10		
W5a (2个)						510	1020	
	31	弹簧垫圈 16	/	16	0.0074	0.2		GB/T859-1987
	30	螺母M16	/	8	0.029	0.3		GB/T6170-2000
	29	螺栓 M16x60	/	8	0.117	1		GB/T5782-2000
	10	-1659.1x5	5858.7	1	411.6	412		花纹钢板冷弯成型
	9	-350x5	1760	1	26.1	26		花纹钢板
	8	-270x5	2470	1	26.2	26		花纹钢板冷弯成型
	7	-160x6	320	2	2.4	5		
	6	-120x6	295	1	1.7	2		
	5	-90x6	1000	1	4.2	4		
	4	-90x6	1050	2	4.5	9		
	3	-90x6	1100	3	4.7	14		
	2	-90x6	1200	2	5.1	10		
W5 (2个)						510	1020	
	31	弹簧垫圈 16	/	16	0.0074	0.2		GB/T859-1987
	30	螺母M16	/	8	0.029	0.3		GB/T6170-2000
	29	螺栓 M16x60	/	8	0.117	1		GB/T5782-2000
	9	-350x5	1760	1	26.1	26		花纹钢板
	8	-270x5	2470	1	26.2	26		花纹钢板冷弯成型
	7	-160x6	320	2	2.4	5		
	6	-120x6	295	1	1.7	2		
	5	-90x6	1000	1	4.2	4		
	4	-90x6	1050	2	4.5	9		
	3	-90x6	1100	3	4.7	14		
	2	-90x6	1200	2	5.1	10		
	1	-1659.1x5	5858.7	1	411.6	412	花纹钢板冷弯成型	
构件号	编号	断 面 尺 寸 (mm)	长 度 (mm)	正 反	单 重	总 重	共 重	备注
				数量		重量 (kg)		
九江石化设计工程有限公司				建设单位	腾龙芳烃(漳州)有限公司			
				项目名称	腾龙芳烃(漳州)80万吨/年对二甲苯工程			
设计			20000m 卷帘型干式 气柜环形走道 W5.5a,6.6a,详图	设计阶段		详细设计		
校核				专 业		设备		
审核				单 元 号				
审定				比 例 1:15				
				D3320-70-00-63-T-101/6-4				